



7051Plus / 5051Plus

Extended Specification

V1.1

Time Electronics, Botany Industrial Estate, Tonbridge, Kent, TN9 1RH England
Tel: 44 (0)1732 355993 Fax: 44 (0) 1732 770312. E-mail: mail@timeelectronics.co.uk
www.timeelectronics.com

SPECIFICATIONS DETAILS

1. Accuracies are shown as \pm (ppm or % of output + floor).
2. Specifications apply for settings between 10% and 100% of range.
3. Specifications apply at ambient temp of $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$
4. For temperatures outside the above range apply $0.2 \times$ specification per $^{\circ}\text{C}$
5. Calibrator warm up time at least 30 minutes.
6. All values are relative to calibration standards.
7. Accuracies quoted are for 1 year.

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Calibrator (Source)

DC VOLTAGE

Range	Accuracy ppm	Output Resistance	Max Output Current	Resolution
20mV	$30 + 4\mu\text{V}$	10Ω	-	100nV
200mV	$30 + 4\mu\text{V}$	10Ω	-	1uV
2V	$15 + 20\mu\text{V}$	$< 0.1 \Omega$	20mA	1uV
20V	$15 + 150\mu\text{V}$	$< 0.1 \Omega$	20mA	10uV
200V	$30 + 3\text{mV}$	$< 5 \Omega$	20mA	100uV
1050V	$50 + 30\text{mV}$	$< 10 \Omega$	10mA	1mV

Specifications are between 0.1Hz and 10Hz bandwidth. Maximum capacitance 1000pF.

AC VOLTAGE

Range	Frequency	Accuracy %	Output Resistance	Max Output Current	Resolution
20mV	10Hz to 45Hz	$0.05 + 250\mu\text{V}$	10Ω	20mA	1uV
	45Hz to 1kHz	$0.05 + 100\mu\text{V}$	10Ω		
	1kHz to 10kHz	$0.05 + 150\mu\text{V}$	10Ω		
	10kHz to 20kHz	$0.05 + 250\mu\text{V}$	10Ω		
	20kHz to 100kHz	$0.05\% + 0.1\text{mV}$	50Ω		
	100kHz to 300kHz	$0.1\% + 0.5\text{mV}$	50Ω		
200mV	10Hz to 45Hz	$0.05 + 250\mu\text{V}$	10Ω	20mA	1uV
	45Hz to 1kHz	$0.04 + 100\mu\text{V}$	10Ω		
	1kHz to 10kHz	$0.04 + 150\mu\text{V}$	10Ω		
	10kHz to 20kHz	$0.05 + 250\mu\text{V}$	10Ω		
	20kHz to 100kHz	$0.1\% + 0.5\text{mV}$	50Ω		
	100kHz to 300kHz	$0.1\% + 1\text{mV}$	50Ω		
2V	10Hz to 45Hz	$0.08 + 500\mu\text{V}$	$< 0.1\Omega$	20mA	10uV
	45Hz to 1kHz	$0.03 + 170\mu\text{V}$	$< 0.1\Omega$		
	1kHz to 10kHz	$0.03 + 250\mu\text{V}$	$< 0.1\Omega$		
	10kHz to 20kHz	$0.08 + 500\mu\text{V}$	$< 0.1\Omega$		
	20kHz to 100kHz	$0.05\% + 1\text{mV}$	$< 0.5\Omega$		
	100kHz to 300kHz	$0.1\% + 5\text{mV}$	$< 0.5\Omega$		
	300kHz to 1MHz	$1\% + 10\text{mV}$	$< 0.5\Omega$		
20V	10Hz to 45Hz	$0.08 + 4\text{mV}$	$< 5\Omega$	20mA	100uV
	45Hz to 1kHz	$0.03 + 2\text{mV}$	$< 5\Omega$		
	1kHz to 10kHz	$0.03 + 3\text{mV}$	$< 5\Omega$		
	10kHz to 20kHz	$0.08 + 4\text{mV}$	$< 5\Omega$		
	20kHz to 100kHz	$0.15\% + 15\text{mV}$			
200V	40Hz to 1kHz	$0.06 + 20\text{mV}$	$< 5\Omega$	20mA	1mV
1050V	40Hz to 1kHz	$0.08 + 90\text{mV}$	$< 10\Omega$	10mA	10mV

The frequency accuracy for AC ranges is 0.01% and is crystal controlled. The setting resolution is 1Hz.

The output resistance on the 20mV and 200mV ranges is 10Ω or 50Ω . This must be taken into account when loads of $100\text{k}\Omega$ or less are being driven. A $100\text{k}\Omega$ load will result in a 0.01% error. All AC outputs exclude the DC component.

DC CURRENT

Range	Accuracy ppm	Compliance Voltage	Resolution
200uA	150 + 15nA	11V	1 nA
2mA	100 + 40nA	11V	10 nA
20mA	80 + 200nA	11V	10 nA
200mA	80 + 3uA	11V	100 nA
2A	250 + 40uA	5V	1 uA
22A	600 + 2mA	4V	10 uA

AC CURRENT (sine wave)

Range	Frequency	Accuracy %	Compliance Voltage	Resolution
200uA	20Hz to 1kHz	0.07 + 300nA	8V rms	10nA
2mA	20Hz to 1kHz	0.05 + 300nA	8V	10nA
20mA	20Hz to 1kHz	0.05 + 3uA	8V	100nA
200mA	20Hz to 1kHz	0.05 + 30uA	8V	1uA
2A	20Hz to 500Hz	0.1 + 0.5mA	3.5V	10uA
22A	20Hz to 500Hz	0.2 + 5mA	3V	100uA

THERMOCOUPLE SIMULATION

Thermocouple Type	Temperature Range °C	Accuracy °C
J	-210 to -50 -50 to 1200	±0.15 ±0.18
K	-270 to 1372	±0.25
T	-270 to -150 -150 to 0 0 to 400	±0.25 ±0.2 ±0.15
R	-50 to 50 50 to 250 250 to 1768	±1.0 ±0.8 ±0.6
S	-50 to 300 300 to 1768	±0.9 ±0.8
B	0 to 800 800 to 1820	±1.8 ±1.0
N	-270 to -100 -100 to 1300	±0.8 ±0.3
E	-270 to -100 -100 to 0 0 to 1000	±0.3 ±0.2 ±0.15

Resolution 0.1°C. Switchable automatic internal cold junction reference, accuracy ±0.5°C (applies to ambient changes of ±1°C)

The accuracy of the thermocouple simulation is determined by the accuracy of the xx51's DC Voltage function and the accuracy of the standard thermocouple tables BS EN 60584-1. The 5051 uses precise digital interpretation of the tables to output voltage levels that are within the accuracies specified in the table above.

RTD SIMULATION

	Range °C	Accuracy °C	Resolution °C
Pt100 (Alpha 0.00385)	-180 to -100 -100 to 850	±0.5 ±0.2	0.01

It should be noted that the accuracy of the RTD simulation is determined by the accuracy of the PRT tables BS EN 60751. The xx51 uses precise digital interpretation of the tables to output resistance values that are within the accuracies specified in the table above

RESISTANCE

Range	Accuracy ¹	Resolution	Max Rating
1Ω to 20Ω	100ppm + 7mΩ	1Ω	0.1W
20Ω to 99.999Ω	100ppm + 7mΩ	1mΩ/5mΩ*	0.1W
100Ω to 999.999Ω	100ppm + 5mΩ	1mΩ	0.1W
1kΩ to 9.999kΩ	200ppm + 20mΩ	1Ω	0.1W
10kΩ to 99.999kΩ	100ppm + 1Ω	1Ω	0.1W
100kΩ to 999.99kΩ	100ppm + 10Ω	10Ω	0.1W
1MΩ to 9.9999MΩ	200ppm + 100Ω	100Ω	0.1W
10MΩ to 120MΩ	0.1% + 1kΩ	1kΩ	0.1W

1.After subtraction of lead resistance. Add end resistance variation ±2.5mΩ. * Output resolution is 5mΩ below 50Ω

CONDUCTANCE

Value	Accuracy	Max Rating
1 S	750ppm	0.1W
100m S	850ppm	0.1W
10m S	250ppm	0.1W
1m S	200ppm	0.1W
100u S	200ppm	0.1W
10u S	200ppm	0.1W
1u S	300ppm	0.1W
100n S	200ppm	0.1W
10n S	210ppm	0.1W
1n S	10%	200V

CAPACITANCE AND INDUCTANCE

Value	Frequency	Accuracy (of displayed value)	Max Volts
1 nF	1kHz	0.5% +/-10pf	25V
10 nF	1kHz	0.5% +/-10pf	
100 nF	1kHz	0.5%	
1 uF	1kHz	0.25%	
10 uF	1kHz	0.5%	
100 uF	100Hz	0.5%	

Value	Frequency	Accuracy (of displayed value)	Max Current
1 mH, 1.9 mH 5 mH, 10 mH 19 mH, 50 mH 100 mH, 190 mH 500 mH, 1H 10H	1kHz 1kHz 1kHz 1kHz 1kHz 100Hz	0.1%	10mA

Specifications apply to the displayed value, after subtraction of residual capacitance / inductance.

Specification based on 4 wire sine-wave measurement technique.

OSCILLOSCOPE / FREQUENCY CALIBRATION

FREQUENCY Fixed Values 1, 2, 5 steps 0.1Hz to 10MHz accuracy 20ppm or 0.1ppm* 20, 50, 100MHz accuracy 20ppm	PERIOD Fixed Values 1, 2, 5 steps 100nS to 10S accuracy 20ppm or 0.1ppm* 50, 20, & 10nS accuracy 20ppm
--	---

* Fitted with Oven-Controlled Frequency Reference (Option 9783)

1.5V pk-pk - 0.1Hz to 100kHz. 1V pk-pk - 100kHz to 100MHz (sine-wave at 100MHz)

DUTY CYCLE

3 frequencies, 100Hz, 1kHz, 10kHz. Duty cycle settable from 0 to 100%

Setting resolution 0.01% at 100Hz, 0.1% at 1 kHz, 1% at 10 kHz

Deviation function is not available.

AMPLITUDE

Output per div	12mV to 50V in 1, 2, 5 sequence. 1kHz square wave or DC.
Graticule X	1, 2, 4, 6, 8. Max output 200V pk-pk 1
Range	Accuracy
6mV to 200mV 200mV to 200V 6mV to 20mV 50Ω 20mV to 2V 50Ω	0.2% +/- 4uV 0.05% 0.5% +/- 10uV 0.25%
FAST RISE	400ps ±150ps (Into 50Ω Load)

1. At 1mV/div 1,2,4X not available

DMM (Measure)

DC VOLTAGE

Range	Accuracy PPM (Reading + Range)	Input Impedance	Resolution
100 mV	50 + 40	10MΩ	1uV
1 V	40 + 8	10MΩ	1uV
10 V	35 + 6	10MΩ	10uV
100 V	45 + 7	10MΩ	100uV
1 kV	45 + 10	10MΩ	1mV

AC VOLTAGE

Range RMS	Frequency	Accuracy % (Reading + Range)	Resolution
100 mV	5 Hz – 10 Hz	0.4 + 0.04	10uV
	10 Hz – 20 kHz	0.06 + 0.04	10uV
	20 Hz – 50 kHz	0.12 + 0.05	10uV
	50 kHz – 100 kHz	0.6 + 0.1	10uV
	100 kHz – 300 kHz	5.0 + 0.5	100uV
1V – 750V	5 Hz – 10 Hz	0.4 + 0.03	0.01% of f.s.
	10 Hz – 20 kHz	0.15 + 0.05	0.01% of f.s.
	20 kHz – 50 kHz	0.6 + 0.1	0.01% of f.s.
	50 kHz – 100 kHz	5.0 + 0.5	0.01% of f.s.

DC CURRENT

Range	Accuracy PPM (Reading + Range)	Burden Voltage	Resolution
10 mA	500 + 200	<0.1V	100nA
100 mA	500 + 50	<0.7V	1uA
1 A	1000 + 100	<1V	10uA
3 A	1200 + 200	<2V	100uA

AC CURRENT

Range	Frequency	Accuracy % (Reading + Range)	Resolution
1 A	10Hz – 5kHz	0.15 + 0.05	100uA
3 A	10Hz – 5kHz	0.25 + 0.1	100uA

RESISTANCE

Range	Test Current	Accuracy (Reading + Range)
100Ω	1mA	100ppm + 40ppm
1kΩ	1mA	100ppm + 10ppm
10kΩ	100uA	100ppm + 10ppm
100kΩ	10uA	100ppm + 10ppm
1 MΩ	5uA	100ppm + 10ppm
10 MΩ	0.5uA	400ppm + 10ppm
100 MΩ	0.1uA	1% + 10ppm

FREQUENCY/PERIOD (100mV to 750V)

Range	Accuracy
3Hz to 10Hz	0.1% of reading
10Hz to 40Hz	0.03% of reading
40Hz to 300kHz	0.01% of reading

THERMOCOUPLES

Thermocouple Type	Temperature Range °C	Accuracy °C
J	-210 to 1200	0.18
K	-270 to 1300	0.4
T	-200 to 380	0.4
R	-50 to 1749	1.0
S	-50 to 1749	1.2
N	-270 to 1280	0.4
E	-50 to 980	0.3

Resolution 0.001°C. Switchable automatic internal cold junction compensation, accuracy ±0.5°C (applies to ambient changes of ±1°C)

RTD

	Range °C	Accuracy °C	Resolution
Pt100 (Alpha = 0.00385 ITS-90 IEC 60751)	-180 to -100 -100 to 550 550 to 850	0.5 0.1 0.15	0.01

Calibrator Options

2.2GHz-LEVELLED SWEEP (9769)

Range	Amplitude Accuracy
100 MHz to 200 MHz	1%
200 MHz to 500 MHz	2%
500 MHz to 1 GHz	4%
1 GHz to 2.2 GHz	6%

1Vpk-pk Sine-Wave, 50Ω Output.

General Specifications

PC SPECIFICATION

Processor	64 bit, quad core (or equivalent)
RAM	4 GB (or higher)
Hard Drive	60 GB Solid State (or higher)
Ports	4 x USB, 1 x Fast Ethernet.
Display	10.4 inch, Touch Screen.
Operating System / Software	Windows 8.1, EasyCal Calibration Software.

POWER SUPPLY

Mains Voltage	100 to 260V AC 50/60 Hz.
Fuse Ratings	3.15A anti-surge
Power Consumption	125W typical, 220W Max.

MAXIMUM ALLOWABLE VOLTAGE BETWEEN TERMINALS

Source	
Between V- and Earth	< 75V Peak
Between Main, Aux and Earth	< 75V Peak
Measure	
Between V+ and V- terminals	<1000V Peak
Between V- and Earth < 75V Peak	<75V Peak

ENVIRONMENTAL

Operating Temperature	5 to 45°C
Storage Temperature	-10°C to 50°C
Humidity	Operating < 80%
Altitude	0 to 3km. Non Operating 3km to 12km
Warm Up Time	30 Minutes

MECHANICAL (5051 only)

Dimensions	Width 430mm, Height 202, Depth 538mm
Weight	23kg