



- Vacuum to 600bar versions available
- Accuracy 0.04% of full scale
- Pneumatic or hydraulic
- 4 selectable pressure units plus mA
- Loop current measure
- 24/36V loop power
- Over-pressure alarm
- RS-232 serial interface
- EasyCal software compatible
- Mains or battery powered

DESCRIPTION

The 7010 is a robust portable pressure calibrator that is suitable for field and laboratory calibration work of both pressure and electrical process loop signals. It is a simple operation instrument ideal for calibrating and cross-checking pressure gauges, sensors, transmitters, transducers, indicators, switches, and many other devices. The following versions are available; 0.2, vacuum to 2, 5, 10, 20, 35, 70, 100, 200, 400, or 600bar. Vacuum down to -850mbar is possible on the 2bar version.

For process signal calibration the loop signal is displayed on the LCD display to 0.05% accuracy. Loop drive supply (24V or 36V) is also provided. Both pressure and loop signal can be displayed at the same time to speed up the calibration of pressure transmitters. Additionally a continuity function is available for testing for open circuit loops.

The 7010 allows switch selection of four pressure units in addition to mA. Common pressure units are configured as standard (see specifications), but user-specified units can be requested:- bar, PSI, kPa, MPa, inWg, cmWg, inHg, mmHg, Kg/cm², atm. Both pressure and loop current are displayed on 4.5 digit LCD displays.

Power is via internal rechargeable cells (24 hours typical use) with a built-in mains charger. The unit can be powered directly from the mains if required. The 7010 is housed in an impact resistant safety case that provides protection and increased durability. All pressure connections are on the side of the case. The instrument is supplied with a pressure hose, electrical test lead, 2 electrical probes and 2 crocodile clips.

OPTIONS

For the 7010, input pressure can be generated by external hand pumps. The 7090 pneumatic (-950mbar to 40bar), or 7095 hydraulic (0 to 700bar) pumps are ideal for this purpose. Gauges are also available.

For process control signal simulation Time Electronics' handheld 7006 Loop-Mate is available as an option. It provides 4 - 20mA and 0 - 10V signals at levels of 0%, 10%, 25%, 50%, 75%, 90%, 100%. It can also step through these set points automatically to allow hands free calibration. It is battery powered and can be stored in the 7010's pouch. See separate datasheets for more information.

The 7010 is fitted with RS-232 connection as standard. Display readback can be performed using EasyCal calibration software. With comprehensive features EasyCal can simplify and speed up calibration procedures. Easily produce calibration certificates and reports to international quality standards.



7010 Specifications

TECHNICAL SPECIFICATION

PRESSURE

Specifications are for 1 year at 23°C ±5°C. Accuracy includes linearity and long term effects. All accuracies are ±1 digit. For operation outside specified temperature range, apply 70ppm per °C

| Range (bar) | 0 to 0.2 | Vac to 2 | 0 to 5 | 0 to 10 | 0 to 20 | 0 to 35 | 0 to 70 | 0 to 100 | 0 to 200 | 0 to 400 | 0 to 600 |
|--------------------|----------|----------|--------|---------|---------|---------|---------|----------|----------|----------|----------|
| Accuracy (% of fs) | 0.1 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.1 | 0.1 | 0.1 |
| Resolution (bar) | 0.01mb | .0001 | 0.001 | 0.001 | 0.001 | 0.01 | 0.01 | 0.01 | 0.01 | 0.1 | 0.1 |

Units 0.2bar: mbar, PSI, kg/cm², cmWg & mA.
 Vac to 2, 5, 10 & 20bar: bar, PSI, kg/cm², cmWg & mA.
 35bar and above: bar, PSI, kg/cm², Atm & mA.
 Maximum Pressure 2 x range, 1.5 x range for 20bar and above
 Sensor Piezo-resistive - stainless steel diaphragm
 Over pressure warning 1.2 x range full scale - audio and visual (on LCD) warning
 Fittings Minimesse (>20bar versions) & Quick Release (<20bar versions)

ELECTRICAL

Range Loop current measurement 0 to 200mA
 Resolution 10µA
 Resistance Loop load 5Ω
 Accuracy 0.05% of reading ±1 digit
 Loop Drive 24V or 36V switch selectable, 50mA max - isolated and with short circuit protection
 Continuity Threshold: 100Ω with audio and visual warning
 Terminals 4mm industry standard terminal posts

GENERAL SPECIFICATION

Power Source Internal rechargeable NiMH batteries, or mains supply (230V or 110V 50/60Hz)
 Battery Life 24 hrs of typical usage between charges
 Display 7 segment LCD with 'Low Battery' warning indicator
 Interfaces RS-232 for readback and re-calibration (software not supplied)
 Case Structural resin which is weather-proof to IP66 standard
 Dimensions W270 x H175 x D250mm
 Weight 3kg
 Supplied with 1 pressure hose: Minimesse for versions ordered over 20bar, Quick release for under 20bar
 Electrical Test Lead: Twin flexible lead, terminated with 4 off 4mm gold plated plugs
 Electrical probes: 2 off low voltage probes and 2 crocodile clips. Mains power lead.
 Optional Extras Pneumatic & hydraulic hand pumps, gauges, loop simulators, EasyCal calibration software, spare fuses, and calibration certificates traceable to NPL and UKAS

ORDERING INFORMATION

7010 **Single Channel Pressure Calibrator** (+ pressure range code shown below)

| Range (bar) | 0.2 | Vac to 2 | 5 | 10 | 20 | 35 | 70 | 100 | 200 | 400 | 600 |
|-------------|------|----------|------|------|------|------|------|------|------|------|------|
| Option Code | 7100 | 7101 | 7102 | 7103 | 7104 | 7105 | 7106 | 7107 | 7108 | 7109 | 7110 |

7090 Pneumatic Hand Pump (-950mbar to 40bar). See separate datasheet for options.
 7095 Hydraulic Hand Pump (0 to 700bar). See separate datasheet for options.
 7006 Loop-Mate 1: Loop Current Simulator
 ECFLA EasyCal Calibration Software. See separate datasheet for further information.
 C178 Factory Calibration Certificate (NPL traceable)
 C190 UKAS Calibration Certificate (ISO 17025)

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Time Electronics Ltd, Unit 11 Sovereign Way, Botany Industrial Estate, Tonbridge, Kent, TN9 1RH. United Kingdom.

T: +44 (0) 1732 355993 F: +44 (0) 1732 770312 E: mail@timeelectronics.co.uk

www.timeelectronics.com

v1d 7/4/13