



- **35, 70, 100, and 200bar versions available**
- **Best accuracy 0.04% of full scale**
- **Pneumatic with regulator**
- **Calibrate gauges, transmitters, sensors**
- **4.5 digit display**
- **5 selectable pressure units**
- **Over-pressure alarm**
- **RS-232 serial interface**
- **EasyCal software compatible**

DESCRIPTION

The 7064 is a high pressure calibration and control module designed for applications up to 200bar. It is fitted with a self-relieving regulator, two needle valves and a dual function front panel pressure port for precision output and measurement. There are four available versions according to required output range, either 35, 70, 100, or 200bar.

The 7064 combines high accuracy with simple operation and is suitable for high volume work in process plants, offshore platforms, refineries, and many other on-site testing facilities. It is ideal for calibration and maintenance of pressure gauges, sensors, transmitters, transducers, indicators, switches, and more.

Features include a 4.5 digit LCD display, 5 pressure units, zeroing switch, regulated output as well as pressure measurement input. Basic accuracy is 0.04% of full scale. Line pressure is supplied via an input minimesse port fitted on the rear of the console. The front panel output and measurement port is also high pressure minimesse type.

The module is fitted as standard with an RS-232 interface which is accessible on the rear of the CalBench console or internally connected to a 7051 calibrator/control centre. This enables communication and read back with EasyCal calibration software (supplied as standard with the 7051 multifunction calibrator/control centre module). With EasyCal the user can define and perform pressure calibration procedures as well as create and print traceable calibration certificates.

SPECIFICATIONS

Specifications are for 1 year at 23°C ±5°C. Accuracy includes linearity and long term effects. All accuracies are ±1 digit. For operation outside specified temperature range, apply 70ppm per °C

Range (bar)	0 to 35	0 to 70	0 to 100	0 to 200
Accuracy (% of fs)	0.04	0.04	0.04	0.1
Resolution (bar)	0.01	0.01	0.01	0.01

Units	bar, PSI, MPa, kg/cm ² , Atm
Maximum Line Pressure	230bar
Sensor	Piezo-resistive - stainless steel diaphragm
Over Pressure Warning	1.2 x range full scale - audio and visual (on LCD) warning
Fittings	Minimesse
Rear Connections	Minimesse
Interface	RS-232 for readback (using EasyCal on 7051 if ordered)
Module Width	200mm (primary or secondary console fitting)

ORDERING INFORMATION

7064 **High Pressure Calibrator Module** (+ pressure range code shown below)

Range (bar)	35	70	100	200
Option Code	7105	7106	7107	7108

ECFLA	EasyCal Calibration Software. See separate datasheet for further information.
C178	Factory Calibration Certificate (NPL traceable)
C190	UKAS Calibration Certificate (ISO 17025)

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.