



- **Temperature accuracy 0.05°C (0.09°F)**
- **Temperature resolution 0.01°C (0.02°F)**
- **Resistance accuracy 0.03Ω**
- **Resistance resolution 0.01Ω**
- **2, 3, and 4 wire connections**
- **Measure and simulate °C, °F, °K, & Ω**
- **Ramp and step**
- **PT100 plus 7 other RTD types**
- **User programmable**

### DESCRIPTION

The 7068 is a process control module that combines a precision digital thermometer (using RTD probes) with an RTD/ohms calibrator.

Easy to use, it solves the problem of making high accuracy temperature measurements without using bulky mains powered instrumentation. It can also be used as an external temperature reference for dry block and other precision temperature baths.

### MODES OF OPERATION

#### Monitor Mode (4 wire)

- Typical Functions .....
1. Check RTD probes by measuring their resistance at known temperatures.
  2. Measure resistance values.
  3. Indicate temperature when connected to an RTD probe.
  4. Can be pre-programmed with a particular RTD's characteristics to allow very high accuracy.

- Excitation current ..... 1mA on all ranges  
 Resistance range ..... 0.01Ω to 2.6kΩ  
 Resolution ..... 0.01Ω  
 Accuracy ..... See specifications on next page  
 Auto re-calibration ..... Every 0.6 secs.  
 Temperature stability ..... Better than 0.0015% per °C  
 Max/Min values ..... Logged automatically

*The 7068 may be used with a calibrated and certified probe to produce a highly accurate thermometer. The performance can be further enhanced by programming the actual characteristic of the probe into the unit.*

#### Simulator Mode (4 wire)

- Typical Functions .....
1. Output resistance of precise known value.
  2. Simulate an RTD value from an RTD table chart.
  3. Simulate an RTD value using the internal table.

- Excitation current ..... 0.6mA to 1mA  
 Resistance range ..... 0.01Ω to 2.6kΩ  
 Resolution ..... 0.01Ω  
 Accuracy ..... See specifications on next page  
 Auto re-calibration ..... Every 0.6 secs.  
 Temperature stability ..... Better than 0.0015% per °C

*Enhanced performance may be achieved by programming the unit to simulate the characteristic of a particular probe. Five fixed step points (0, 25, 50, 75, 100%) are available between a user set minimum (0%) and a maximum (100%). Programmable ramp function is also available.*

# 7068 Specifications

## TECHNICAL SPECIFICATIONS

Standard RTD types (Non standard RTD types user programmable)

Element	Alpha Coefficient	Temp Range °C	Accuracy °C	Temp Range °F	Accuracy °F
Pt100 DIN	0.003850	-200 to 250	0.05	-330 to 480	0.10
		250 to 849	0.07	480 to 1560	0.14
Pt100 US	0.003916	-100 to 250	0.05	-150 to 480	0.10
		250 to 457	0.07	480 to 850	0.14
Pt200 DIN	0.003850	-200 to 300	0.05	-330 to 570	0.10
Pt500 DIN	0.003850	-200 to 250	0.05	-330 to 480	0.10
		250 to 630	0.07	480 to 1160	0.14
Pt1000 DIN	0.003850	-200 to 250	0.05	-330 to 480	0.10
		250 to 630	0.07	480 to 1160	0.14
Ni 120	0.006180	-100 to 200	0.05	-150 to 390	0.10
Ni 1000	0.006180	-100 to 200	0.05	-150 to 390	0.10

### Resistance Accuracy

Range ohms	Monitor	Generator
20 to 400	0.03Ω	0.03Ω
400 to 800	0.10Ω	0.10Ω
800 to 1200	0.20Ω	0.20Ω
1200 to 2600	0.50Ω	0.50Ω*

\*plus additional error of 0.05% of output value. If excitation current is less than 1mA.

## GENERAL SPECIFICATION

Operating temperature range ..... -10 to 50°C  
 Module Dimensions ..... H201 x W107mm (primary or secondary console fitting)  
 Optional Extras ..... Calibration certificates traceable to NPL and UKAS

## ORDERING INFORMATION

7068 ..... RTD Temperature Calibrator Module  
 C183 ..... Factory (NPL traceable) Calibration Certificate  
 C194 ..... UKAS Calibration Certificate (ISO 17025)

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Time Electronics Ltd, Unit 11 Sovereign Way, Botany Industrial Estate, Tonbridge, Kent, TN9 1RH. United Kingdom.

T: +44 (0) 1732 355993 F: +44 (0) 1732 770312 E: mail@timeelectronics.co.uk

[www.timeelectronics.com](http://www.timeelectronics.com)